

Advanced

Default Settings

Default Settings used for all domains. Branding can be done in this section, [see here to adjust](#) or copy settings to specific domains.

Default Settings

Settings used for all domains.

Provision

COPY

TOGGLE

RELOAD

Provision

Subcategory	Type	Value	Enabled	Description	+	x
<input type="checkbox"/> aastra_date_format	numeric	0	True	Aastra date format		
<input type="checkbox"/> aastra_gmt_offset	numeric	0	True	Aastra timezone offset in minutes (e...		
<input type="checkbox"/> aastra_time_format	numeric	0	True	Aastra clock format		
<input type="checkbox"/> admin_name	text		False			
<input type="checkbox"/> admin_password	text		False			
<input type="checkbox"/> auto_insert_enabled	boolean	true	False			
<input type="checkbox"/> cidr	array		False			
<input type="checkbox"/> contact_extensions	boolean	true	False	allow extensions to be provisioned ...		
<input type="checkbox"/> contact_grandstream	boolean	true	False	Enable Address Book for Grandstre...		
<input type="checkbox"/> contact_groups	boolean	true	False			
<input type="checkbox"/> contact_users	boolean	true	False			
<input type="checkbox"/> daylight_savings_enabled	boolean	true	True			
<input type="checkbox"/> daylight_savings_start_day	text	12	True			
<input type="checkbox"/> daylight_savings_start_month	text	3	True			
<input type="checkbox"/> daylight_savings_start_time	text	2	True			

Default Settings have several different categories. Click on the category to view more details.

Cache

Option to use file cache for xml and not memcache.

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
method	text	memcache	TRUE	Cache methods file or memcache.
location	text	/tmp	TRUE	Location for the file cache.

Call Center

FusionPBX menu [Apps > Call Center](#)

Defaults for the amount of agent rows for Call Center.

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
agent_add_rows	numeric	5	TRUE	Number of default "add" rows.
agent_edit_rows	numeric	1	TRUE	Number of default "edit" rows.

CDR

FusionPBX menu [Apps > CDR](#)

CDR Stat hour limit, call leg, format, limit, http_enabled, archive database, and storage type settings can be set here.

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
stat_hours_limit	numeric	24	FALSE	
b_leg	array	outbound	FALSE	
b_leg	array	inbound	FALSE	
b_leg	array	local	FALSE	
format	text	json	TRUE	
limit	numeric	800	TRUE	
http_enabled	boolean	TRUE	TRUE	
archive_database_driver	text	pgsql	FALSE	Archive Database Driver
archive_database_host	text		FALSE	IP/Hostname of Archive Database
archive_database_password	text		FALSE	Archive Database Password
archive_database_port	text	5432	FALSE	Archive Database Port
archive_database_username	text		FALSE	Archive Database Username
storage	text	db	TRUE	
archive_database	boolean	FALSE	FALSE	Enable Dedicated CDR Database Access
archive_database_name	text	fusionpbx	FALSE	Archive Database Name

Dashboard

FusionPBX menu [Home > Dashboard](#)

Different user level settings that control what is seen and not seen on the dashboard for each user access level.

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
admin	array	voicemail	TRUE	Enable Dashboard Voicemail block for users in the admin group.
admin	array	missed	TRUE	Enable Dashboard Missed Calls block for users in the admin group.
admin	array	recent	TRUE	Enable Dashboard Recent Calls block for users in the admin group.
admin	array	limits	FALSE	Enable Dashboard Domain Limits block for users in the admin group.
admin	array	counts	TRUE	Enable Dashboard Domain Counts block for users in the admin group.
admin	array	ring_groups	TRUE	Enable Dashboard Ring Group Forwarding controls for users in the admin group.
admin	array	caller_id	FALSE	Enable changing Caller ID name and number.
superadmin	array	voicemail	TRUE	Enable Dashboard Voicemail block for users in the superadmin group.
superadmin	array	missed	TRUE	Enable Dashboard Missed Calls block for users in the superadmin group.
superadmin	array	recent	TRUE	Enable Dashboard Recent Calls block for users in the superadmin group.
superadmin	array	limits	FALSE	Enable Dashboard Domain Limits block for users in the superadmin group.
superadmin	array	counts	TRUE	Enable Dashboard System Counts block for users in the superadmin group.
superadmin	array	call_routing	TRUE	Enable Dashboard Call Routing controls for users in the superadmin group.
superadmin	array	caller_id	FALSE	Enable changing Caller ID name and number.

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
superadmin	array	ring_groups	TRUE	Enable Dashboard Ring Group Forwarding controls for users in the superadmin group.
user	array	voicemail	TRUE	Enable Dashboard Voicemail block for users in the users group.
user	array	missed	TRUE	Enable Dashboard Missed Calls block for users in the users group.
user	array	recent	TRUE	Enable Dashboard Recent Calls block for users in the users group.
user	array	call_routing	TRUE	Enable Dashboard Call Routing controls for users in the users group.
user	array	ring_groups	TRUE	Enable Dashboard Ring Group Forwarding controls for users in the users group.
user	array	caller_id	FALSE	Enable changing Caller ID name and number.
admin	array	call_routing	TRUE	Enable Dashboard Call Routing controls for users in the admin group.
superadmin	array	system	TRUE	Enable Dashboard System Status block for users in the superadmin group.
agent	array	call_center_agents	TRUE	Enable Dashboard Call Center Agent Status block for users in the agent group.

[Destinations](#)

FusionPBX menu [Dialplan > Destinations](#)

Destinations specific defaults.

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
dialplan_details	boolean	TRUE	TRUE	

Domains

FusionPBX menu [Advanced > Domains](#)

Domain specific defaults.

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
dial_string	text	{sip_invite_domain=\${domain_name},leg_timeout=\${call_timeout},presence_id=\${dialled_user}@\${dialled_domain}}\$ {sofia_contact(*\${dialled_user}@\${dialled_domain})}	TRUE	The dial string used
template	name	default	TRUE	The template used
menu	uuid	b4750c3f-2a86-b00d-b7d0-345c14eca286	TRUE	The menu uuid
language	code	en-us	TRUE	Choose the language
cidr	array		FALSE	Allow only specific ip addresses access
country	code	us	TRUE	The country code
bridge	text	outbound	TRUE	outbound,loopback,lcr
paging	numeric	100	TRUE	Set the maximum number of records displayed per page. (Default: 50)
time_zone	name	America/Los_Angeles	TRUE	Time zone used. Follows UNIX format

Editor

FusionPBX menu Advanced > php editor, grammar editor, provision editor, and xml editor.

Editor specific defaults.

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
indent_guides	boolean	FALSE	FALSE	Set the default visibility of indent guides for Editor.
invisibles	boolean	FALSE	FALSE	Set the default state of invisible characters for Editor.
line_numbers	boolean	FALSE	FALSE	Set the default visibility of line numbers for Editor.
theme	text	Cobalt	FALSE	Set the default theme.
font_size	text	14px	FALSE	Set the default text size for Editor.
live_previews	boolean	FALSE	FALSE	Enable or disable live previewing of syntax, text size and theme changes.

Email

This is where you configure email settings to receive email notifications of voicemail, missed calls and fax.

Here are some example settings for some of the most common email providers.

- [SMTP2GO](#)
- [GMAIL](#)

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
smtp_host	text	mail.server.provider.com	TRUE	email providers server address
smtp_from	text	email@example.com	TRUE	smtp from email address
smtp_port	numeric	587	TRUE	port number of the mail server provider
smtp_from_name	text	Voicemail	TRUE	smtp from name
smtp_auth	text	TRUE	TRUE	If smtp auth is required
smtp_username	text	user name	TRUE	typically the email user name
smtp_password	text	supersecurepassword!	TRUE	typically the email password
smtp_secure	text	tls	TRUE	tls or ssl depending on the provider.
smtp_validate_certificate	boolean	TRUE	TRUE	set to false to ignore SSL certificate warnings e.g. for self-signed certificates
method	text	smtp	TRUE	smtp sendmail mail

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
				lqmail

Error log for failed or successfully sent messages.

- [Email Log](#)

Fax

[Apps > Fax Server](#)

Specific default settings for fax server.

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
cover_logo	text		TRUE	Path to image/logo file displayed in the header of the cover sheet.
allowed_extension	array	.pdf	TRUE	Allowed extension to send .pdf
allowed_extension	array	.tif	TRUE	Allowed extension to send .tif
allowed_extension	array	.tiff	TRUE	Allowed extension to send .tiff
cover_header	text		FALSE	Default information displayed beneath the logo in the header of the cover sheet.
page_size	text	letter	TRUE	Set the default page size of new faxes.
resolution	text	fine	TRUE	Set the default transmission quality of new faxes.
variable	array	fax_enable_t38=true	TRUE	Enable T.38.
variable	array	fax_enable_t38_request=false	TRUE	Send a T38 reinvite when a fax tone is detected.
variable	array	ignore_early_media=true	TRUE	Ignore ringing to improve fax success rate.
keep_local	boolean	TRUE	TRUE	Keep the file after sending or receiving the fax.
send_mode	text	queue	FALSE	Send mode. queue is default.
send_retry_limit	numeric	5	TRUE	Number of attempts to send fax (count only calls with

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
				answer).
send_retry_interval	numeric	15	TRUE	Delay before we make next call after answered call.
send_no_answer_retry_limit	numeric	3	TRUE	Number of unanswered attempts in sequence.
send_no_answer_retry_interval	numeric	30	TRUE	Delay before we make next call after no answered call.
send_no_answer_limit	numeric	3	TRUE	Giveup reach the destination after this number of sequences.
send_no_answer_interval	numeric	300	TRUE	Delay before next call sequence.
storage_type	text	base64	FALSE	Store FAX in base64.
smtp_from	text		TRUE	SMTP from address.
smtp_from_name	text		TRUE	SMTP from name. Depends on the server, can be full email or everything before the @ sign.
cover_font	text	times	FALSE	Font used to generate cover page. Can be full path to .ttf file or font name already installed.
cover_footer	text		TRUE	Notice displayed in the footer of the cover sheet.

Follow Me

FusionPBX menu [Apps > Follow Me](#)

Specific defaults for Follow Me.

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
max_destinations	numeric	5	FALSE	Set the maximum number of Follow Me Destinations.
timeout	numeric	30	FALSE	Set the default Follow Me Timeout value.

Advanced

[Ivr Menu](#)

FusionPBX menu [Apps > IVR Menus](#)

Specific default for IVR Menu.

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
option_add_rows	numeric	5	TRUE	Number of default "add" rows.
option_edit_rows	numeric	1	TRUE	Number of default "edit" rows.

[Limit](#)

Limit specific default settings.

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
call_center_queues	numeric	3	FALSE	Limit used in Call Center Queues.
destinations	numeric	3	FALSE	Limit used in Destinations.
devices	numeric	3	FALSE	Limit used in Devices.
extensions	numeric	3	FALSE	Limit used in Extensions.
gateways	numeric	3	FALSE	Limit used in Gateways.
ivr_menus	numeric	3	FALSE	Limit used in IVR Menus.
ring_groups	numeric	3	FALSE	Limit used in Ring Groups.
users	numeric	3	FALSE	Limit used in Users.

[Login](#)

Login specific default settings.

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
password_reset_key	text	9pG6sgerhuh5hetjn srtjrjrdW	FALSE	Display a Reset Password link on the login box (requires smtp_host be defined).
domain_name_visible	boolean	TRUE	FALSE	Displays a domain input or select box

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
				(if domain_name array defined) on the login box.
domain_name	array	pbx1.yourdomain.com	FALSE	Domain select option displayed on the login box.
message	text	Welcome to FusionPBX!	TRUE	Display a message at login.

Provision

In the Provisioning section, there are a few key options that have to be set in order to turn auto provisioning on.

- **enabled:** Must be enabled and set to **value true** and **enabled True**. It is disabled by default.
- **http_auth_username:** Must be enabled and set to **value true** and **enabled True**. It is disabled by default. Be sure to use a strong username.
- **http_auth_password:** Must be enabled and set to **value true** and **enabled True**. It is disabled by default. Be sure to use a strong password.

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
fanvil_time_zone	text	-20	TRUE	Time zone ranges
fanvil_time_zone_name	text	UTC-5	TRUE	Time zone name example United States-Eastern Time
fanvil_location	numeric	4	TRUE	Used with time zone and time zone name
fanvil_realm	text	enter a value	FALSE	enter a value
fanvil_greeting	text	FusionPBX	TRUE	Name at top left of screen 0~12 characters
fanvil_date_display	numeric	3	TRUE	value 0-13 Date Format
fanvil_time_display	numeric	1	TRUE	1=12hr 0=24hr
fanvil_wifi_enable	numeric	0	TRUE	1=on 0=off
fanvil_stun_port	numeric	3478	TRUE	enter a stun port number
grandstream_call_waiting	text	0	TRUE	Call Waiting 0=enabled 1=disable
contact_grandstream	boolean	TRUE	FALSE	Enable Address Book for Grandstream based on users and groups assigned to contact.
grandstream_gxp_time_zone	text	auto	TRUE	See provision profile for codes.
grandstream_check_sip_user_id	text	1	TRUE	GXV Android phones - fix auto-

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
				ring bug.
grandstream_config_server_path	text	none	FALSE	mydomain.com/app/provision to Fusionpbx provisioning. Phones will use firmware url if this is set to: none
grandstream_firmware_path	text	mydomain.com/app/provision	TRUE	Grandstream firmware and provision.
grandstream_lan_port_vlan	text	1	FALSE	Default VLAN for phone LAN port.
grandstream_pc_port_vlan	text	1	FALSE	Default VLAN for phone PC port.
grandstream_ldap_base_dn	text	dc=mydomain,dc=com	FALSE	Base DN
grandstream_ldap_display_name	text	givenName sn title	FALSE	Which named attributes to display on device. Must be pulled in through grandstream_ldap_name_attr.
grandstream_ldap_mail_attr	text	mail	FALSE	Mail attribute returned to phone
grandstream_ldap_mail_filter	text	(mail=%)	FALSE	Search filter for mail lookups
grandstream_ldap_name_attr	text	givenName sn title mail	FALSE	The NAME attributes returned in the LDAP search result available to device
grandstream_ldap_name_filter	text	(cn=%)	FALSE	Search filter for name lookups
grandstream_ldap_number_attr	text	telephoneNumber mobile homePhone	FALSE	Number attributes returned to the phone.
grandstream_ldap_number_filter	text	(↓ (telephoneNumber=%)(homePhone=%)(mobile=%%))	FALSE	Search filter for number lookups.
grandstream_ldap_password	text	super-secret	FALSE	Ldap bind user password.
grandstream_ldap_server	text	mydomain.com	FALSE	Ldap server host name
grandstream_ldap_user_base	text	ou=users,dc=mydomain,dc=com	FALSE	Ldap base for users.
grandstream_ldap_username	text	cn=pbxadmin,dc=mydomain,dc=com	FALSE	Ldap server bind username
grandstream_phonebook_download_interval	text	720	TRUE	0=disabled, 5-720 minutes
grandstream_qos RTP	text	5	FALSE	Layer 2 QoS 802.1p Priority Value for RTP media
grandstream_qos SIP	text	3	FALSE	Layer 2 QoS 802.1p Priority Value for

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
				SIP signaling
grandstream_sip_ontext ly_known_servers		1	TRUE	GXV Android phones - fix auto-ring bug.
grandstream_stun_stext server		mydomain.com	TRUE	Bug in Grandstream where null stun_server defaults to sip server/port
grandstream_validatext te_incoming_sip		1	TRUE	GXV Android phones - fix auto-ring bug.
grandstream_wallpatext per_url		https://mydomain.com/files/wallpaper.jpg	FALSE	Wallpaper Image JPEG 480x272 16-bit depth dithered
grandstream_bluetotext oth_power		1	FALSE	Bluetooth Power - 0 - Off, 1 - On, 2 - Off & Hide Menu From LCD
grandstream_bluetotext oth_handsfree		1	FALSE	Bluetooth Handsfree - 0 - Off, 1 - On
grandstream_autotext attended_transfer		1	TRUE	Attended Transfer Mode. 0 - Static, 1 - Dynamic. Default is 0
grandstream_syslogtext _server			FALSE	Syslog Server (name of the server, max length is 64 characters)
grandstream_syslogtext _level		0	FALSE	Syslog Level. 0 - NONE, 1 - DEBUG, 2 - INFO, 3 - WARNING, 4 - ERROR. Default is 0
grandstream_sendtext sip_log		0	FALSE	Send SIP Log. 0 - Do not send SIP log in Syslog, 1 - Send SIP log in Syslog if configured and set to DEBUG level. Default is 0
grandstream_screetext nsaver		1	TRUE	Screensaver. 0 - No, 1 - Yes, 2 - On if no VPK is active. Default is 1
grandstream_screetext nsaver_source		0	TRUE	Screensaver Source. 0 - Default, 1 - USB, 2 - Download. Default is 0. -for GXP2140/2160/2170 only
grandstream_screetext nsaver_show_date_time		1	TRUE	Show Date and Time. 0 - No, 1 - Yes. Default is 1
grandstream_screetext nsaver_timeout		5	TRUE	Screensaver Timeout. Minutes

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
				3-60
grandstream_screensaver_server_path	text		FALSE	Screensaver Server Path
grandstream_screensaver_xml_download_interval	text	0	FALSE	Screensaver XML Download Interval Number: 5 - 720. Default is 0 (disable auto downloading)
grandstream_srtp	text	0	TRUE	SRTP Mode. 0 - Disabled, 1 - Enabled but not forced, 2 - Enabled and forced, 3 - Optional. Default is 0
htek_time_zone	text	18	TRUE	Time zone 18=EST 14=CST 6=PST 9,10=MST
htek_dst	numeric	1	TRUE	DST off=0 on=1 auto=2
htek_date_display_format	numeric	1	TRUE	Year-Month-Day=0 Month-Day-Year=1 Day-Month-Year=2
htek_time_format	numeric	1	TRUE	1=12hr 0=24hr
polycom_digitmap	text	[*]xxxx [2-9]11 0T 011xxx.T [0-1][2-9]xxxxxxxx [2-9]xxx xxxxxx [1-9]xxT **x.T	FALSE	
polycom_call_waiting	text	1	TRUE	Call Waiting 1=enabled 0=disable
cidr	array	209.210.17.193/32	FALSE	
http_auth_username	text	admin	TRUE	
http_auth_type	text	digest	TRUE	
enabled	text	TRUE	TRUE	
cidr	array	209.210.16.196/32	FALSE	
auto_insert_enabled	boolean	TRUE	FALSE	
http_auth_disable	boolean	FALSE	FALSE	
admin_name	text		FALSE	
admin_password	text		FALSE	
path	text		FALSE	
outbound_proxy_primary	text		FALSE	
outbound_proxy_secondary	text		FALSE	
line_sip_port	numeric	5060	TRUE	
line_sip_transport	text	tcp	TRUE	
daylight_savings_enabled	boolean	TRUE	TRUE	
daylight_savings_start_month	text	3	TRUE	
daylight_savings_start_weekday	text	7	TRUE	
daylight_savings_start_time	text	2	TRUE	

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
daylight_savings_start_weekday	text	7	TRUE	
daylight_savings_start_time	text	2	TRUE	
http_domain_filter	boolean	TRUE	TRUE	
contact_users	boolean	TRUE	FALSE	
contact_groups	boolean	TRUE	FALSE	
number_as_presence_id	text	TRUE	TRUE	
ntp_server_primary	text	pool.ntp.org	TRUE	
ntp_server_secondary	text	2.us.pool.ntp.org	TRUE	
spa_time_zone	text	GMT-07:00	TRUE	
spa_time_format	text	12hr	TRUE	12hr,24hr
spa_date_format	text	day/month	TRUE	
spa_back_light_timer	text	30 s	TRUE	
spa_handle_via_report	text	Yes	TRUE	
spa_insert_via_report	text	Yes	TRUE	
spa_call_waiting	text	Yes	TRUE	Call Waiting Yes=enabled No=disable
spa_feature_key_sync	text	No	TRUE	Feature Key Sync Yes=enabled No=disable
spa_dual_registration	text	No	TRUE	Dual Registration Yes=enabled No=disable
spa_register_when_failover	text	No	TRUE	Auto register when failover Yes=enabled No=disable
snom_call_waiting	text	on	TRUE	Call Waiting on=enabled off=disable visual only and ringer
nway_conference	text	TRUE	FALSE	N-Way conferencing for devices supporting network conference uri
vtech_vlan_wan_enabled	text	0	FALSE	Enable vlan=1
vtech_vlan_wan_id	text	1	FALSE	VLAN ID
vtech_vlan_wan_priority	text	0	FALSE	VLAN Priority
stun_server	text		FALSE	STUN server address
stun_port	numeric	3478	FALSE	STUN server port
aastra_gmt_offset	numeric	0	TRUE	Aastra timezone offset in minutes (e.g. 300 = GMT-5 = Eastern Standard Time)
aastra_time_format	numeric	0	TRUE	Aastra clock format
aastra_date_format	numeric	0	TRUE	Aastra date format
yealink_time_zone	text	-5	FALSE	Time zone ranges

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
				from -11 to +12
yealink_time_zone_name	text	United States-Eastern Time	FALSE	Time zone name example United States-Mountain Time
yealink_time_format	text	1	FALSE	0-12 Hour, 1-24 Hour
yealink_rport	boolean	1	TRUE	Send the response back to the source it came from.
yealink_session_timer	boolean	0	TRUE	SIP Session Timers
yealink_retransmission	boolean	0	TRUE	Retransmission
yealink_subscribe_mwi_to_vm	boolean	1	TRUE	subscribe to the voicemail MWI 0-Disabled (default), 1-Enabled
yealink_srtp_encryption	text	0	TRUE	
yealink_rfc2543_hold	numeric	0	FALSE	Default 0
yealink_blf_led_mode	numeric	0	FALSE	The value is 0(default) or 1.
yealink_trust_ctrl	numeric	1	TRUE	(0-Disabled;1-Enabled)
yealink_direct_ip_call_enable	numeric	0	FALSE	(0-Disabled;1-Enabled)
yealink_hide_feature_access_codes_enable	numeric	0	FALSE	(0-Disabled;1-Enabled)
yealink_voice_mail_popup_enable	numeric	0	FALSE	Display Voice Mail Popup
yealink_missed_call_popup_enable	numeric	0	FALSE	Display Missed Call Popup
yealink_cid_source	numeric	0	TRUE	The type of SIP header(s) to carry the caller ID; 0-FROM (default), 1-PAI 2-PAI-FROM, 3-PRID-PAI-FROM, 4-PAI-RPID-FROM, 5-RPID-FROM
yealink_dtmf_hide	numeric	1	TRUE	0-Disabled 1-Enabled
yealink_sip_listen_port	numeric	5060	FALSE	5060 default
yealink_firmware_url	text	https://server.yourdomain.com/app/yealink/resources/firmware	TRUE	Base URL for Yealink Firmware. Download from http://support.yealink.com
yealink_firmware_cp860	text	cp860-37.81.0.10.rom	TRUE	Filename of the CP860 firmware ROM
yealink_firmware_cp960	text	cp960-73.80.0.25.rom	TRUE	Filename of the

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
CP960		m		CP960 firmware ROM
yealink_firmware_t29g	text	t29g-46.81.0.110.rom	TRUE	Filename of the T29G firmware ROM
yealink_firmware_t38g	text	t38g-38.70.0.185.rom	TRUE	Filename of the T38G firmware ROM
yealink_firmware_t40g	text	t40g-76.81.0.110.rom	TRUE	Filename of the T40G firmware ROM
yealink_firmware_t40p	text	t40p-54.81.0.110.rom	TRUE	Filename of the T40P firmware ROM
yealink_firmware_t41s	text	t41s-66.81.0.110.rom	TRUE	Filename of the T41S firmware ROM
yealink_firmware_t42g	text	t42g-29.81.0.110.rom	TRUE	Filename of the T42G firmware ROM
yealink_firmware_t42s	text	t42s-66.81.0.110.rom	TRUE	Filename of the T42S firmware ROM
yealink_firmware_t46g	text	t46g-28.81.0.110.rom	TRUE	Filename of the T46G firmware ROM
yealink_firmware_t46s	text	t46s-66.81.0.110.rom	TRUE	Filename of the T46S firmware ROM
yealink_firmware_t48g	text	t48g-35.81.0.110.rom	TRUE	Filename of the T48G firmware ROM
yealink_firmware_t48s	text	t48s-66.81.0.110.rom	TRUE	Filename of the T48S firmware ROM
yealink_firmware_t49g	text	t49g-51.80.0.100.rom	TRUE	Filename of the T49G firmware ROM
yealink_firmware_t54s	text	T54S(T52S)-70.82.0.20.rom	TRUE	Firmware tested 2017-11-26
yealink_firmware_t56a	text	t56a-58.80.0.25.rom	TRUE	Filename of the T56A firmware ROM
yealink_firmware_t58a	text	t58a-58.80.0.25.rom	TRUE	Filename of the T58A firmware ROM
yealink_firmware_t58v	text	t58v-58.80.0.25.rom	TRUE	Filename of the T58V firmware ROM
yealink_firmware_vp530	text	vp530-23.70.0.40.rom	TRUE	Filename of the VP530 firmware ROM
yealink_network_vpn_enable	boolean	1	FALSE	(0-Disabled;1-Enabled)
yealink_ip_address_mode	numeric	0	FALSE	IP Address mode 0-ipv4, 1-ipv6, 2-ipv4&ipv6
yealink_lldp_enable	boolean	0	FALSE	LLDP 0-Disabled, 1-Enabled
yealink_cdp_enable	boolean	0	FALSE	CDP 0-Disabled, 1-Enabled
yealink_overwrite_mode	boolean	0	TRUE	Overwrite Mode 0-Disabled, 1-Enabled
yealink_dsskey_length	numeric	0	TRUE	DSS Key Label Length Default-0 Extended-1 Mid Range-2
yealink_feature_key_sync	numeric	0	TRUE	Enable or disable the feature key synchronization; 0-Disabled (default)

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
				1-Enabled
yealink_predial_auto_dial	boolean	0	TRUE	Auto dial after digit timeout 0-Disabled (default), 1-Enabled;
yealink_ring_type	text	custom.wav	FALSE	custom ring tone (Busy.wav);
yealink_rington_delete	text	http://localhost/all.delete	FALSE	http://localhost/all.delete all the customized ring tones
daylight_savings_start_day	text	11	TRUE	
daylight_savings_start_month	text	11	TRUE	
daylight_savings_start_day	text	4	TRUE	
http_auth_password	array	555	TRUE	
fanvil_stun_server	text	example.domain.tld	FALSE	enter a server name or ip
grandstream_dns_mode	text	1	FALSE	DNS Mode 0=A; 1=SRV; 2=NAPTR/SRV;
grandstream_global_contact_groups	text	contacts_elementary,contacts_facilities,contacts_other,contacts_secondary	FALSE	List of contact groups that every phone will have access to. Namely building sites.
grandstream_nat_traversal	text	0	TRUE	NAT Traversal. 0 - No, 1 - STUN, 2 - keep alive, 3 - UPnP, 4 - Auto, 5 - VPN
grandstream_phonebook_xml_server_path	text	mydomain.com/app/provision/pb/	TRUE	Grandstream Phonebook Server Path - NOTE template adds MAC on the end of this if contact_grandstream is enabled. This also requires nginx rewrite rules for phonebook.xml
polycom_gmt_offset	text		FALSE	3600 * GMT offset
polycom_feature_key_sync	numeric	0	TRUE	Feature Key Sync 1=enabled 0=disable
voicemail_number	text	*97	TRUE	
line_register_expires	numeric	120	TRUE	
contact_extensions	boolean	TRUE	FALSE	allow extensions to be provisioned as contacts as in provision templates
spa_dial_plan	text	(xxxxxxx *xxxxxx *xxxx *xxxx *xxx *x	TRUE	

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
		x* *x **xxxxx **xxx x **xxx **xx [3469] 11 0 00 [2-9]xxxxxx 1xxx[2-9]xxxxxxS0 xxxxxxxxxxxxxx.)		
spa_secure_call_set ting	text	No	TRUE	spa secure call No or Yes
snom_time_zone	text	USA-7	FALSE	http://wiki.snom.com/Settings/timezone
yealink_date_format	text	3	FALSE	0-WWW MMM DD (default), 1-DD- MMM-YY, 2-YYYY- MM-DD, 3-DD/MM/YYYY, 4-MM/DD/YY, 5-DD MMM YYYY, 6-WWW DD MMM
yealink_outbound_p roxy_fallback_interv al	numeric	3600	FALSE	Integer from 0 to 65535
yealink_missed_call _power_led_flash_e nable	numeric	0	FALSE	(0-Disabled:power indicator LED is off;1-Enabled:power indicator LED is solid red)
yealink_firmware_t4 1p	text	t41p-36.81.0.110.ro m	TRUE	Filename of the T41P firmware ROM
yealink_firmware_t5 2s	text	t52s-70.81.0.10.ro m	TRUE	Filename of the T52Sfirmware ROM
yealink_openvpn_ur l	text	hxxps://replace-this .url/openvpn.tar	FALSE	(URL within 511 characters)
yealink_ringtone_ur l	text	custom.wav	FALSE	Before using this parameter, you should store the desired ring tone (custom.wav) to the provisioning server
yealink_call_waiting	text	0	TRUE	Call Waiting 1=enabled 0=disable
grandstream_dial_pl an	text	{x+ *x+ *++ park +*x+ flow+*x+}	TRUE	Define the digits that are allowed to be called.

Recordings

FusionPBX menu [Apps > Recordings](#)

Recordings specific default settings.

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
storage_type	text	base64	FALSE	Save recordings in the database in base64 format.

Ring Group

FusionPBX menu [Apps > Ring Group](#)

Ring Groups specific default settings.

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
destination_add_rows	numeric	5	TRUE	Ring Group “add” rows default.
destination_edit_rows	numeric	1	TRUE	Ring Group “edit” rows default.

Security

Security specific default settings.

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
password_length	numeric	15	TRUE	Set the required length for the generated passwords.
password_number	boolean	TRUE	FALSE	Set whether to require at least one number in passwords.
password_uppercase	boolean	TRUE	FALSE	Set whether to require at least one uppercase letter in passwords.
password_special	boolean	TRUE	FALSE	Set whether to require at least one special character in passwords.
session_rotate	boolean	TRUE	TRUE	Whether to regenerate the session ID.
password_lowercase	boolean	TRUE	TRUE	Set whether to require at least one lowercase letter in passwords.
password_strength	numeric	4	TRUE	Set the default strength for

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
				generated passwords. Valid Options: 1 - Numeric Only, 2 - Include Lower Alpha, 3 - Include Upper Alpha, 4 - Include Special Characters.

Server

Server specific default settings.

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
temp	text	/tmp	TRUE	Set the temp directory.

Switch

Switch specific default settings. These defaults will change depending if you compiled the SWITCH source or used the newest default of packages.

default_setting_subcategory	default_setting_name	default_setting_value	default_setting_enabled	default_setting_description
bin	dir		TRUE	Server path for bin.
base	dir	/usr	TRUE	Server path for base.
call_center	dir	/etc/freeswitch/auto load configs	FALSE	Server path for Call Center.
conf	dir	/etc/freeswitch	TRUE	Server path for Conf files.
db	dir	/var/lib/freeswitch/db	TRUE	Server path for sqlite db files.
dialplan	dir	/etc/freeswitch/dialplan	FALSE	Server path for xml dialplan
extensions	dir	/etc/freeswitch/directory	FALSE	Server path for extension directory.
grammar	dir	/usr/share/freeswitch/grammar	TRUE	Server path for grammar xml.
log	dir	/var/log/freeswitch	TRUE	Server path for SWITCH logs.
mod	dir	/usr/lib/freeswitch/mod	TRUE	Server path for SWITCH mod's.
phrases	dir	/etc/freeswitch/lang	TRUE	Server path for SWITCH xml phrases.
recordings	dir	/var/lib/freeswitch/r	TRUE	Server path for

Advanced

default_setting_subcategory	default_setting_name	default_setting_value	default_setting_enabled	default_setting_description
		recordings		SWITCH recordings.
scripts	dir	/usr/share/freeswitch/scripts	TRUE	Server path for SWITCH scripts.
sip_profiles	dir	/etc/freeswitch/sip_profiles	FALSE	Server path for SWITCH xml sip profiles.
sounds	dir	/usr/share/freeswitch/sounds	TRUE	Server path for SWITCH sounds.
storage	dir	/var/lib/freeswitch/storage	TRUE	Server path for SWITCH storage.
voicemail	dir	/var/lib/freeswitch/storage/voicemail	TRUE	Server path for SWITCH voicemails.

Theme

Theme specific default settings.

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
background_image	array	/themes/default/images/backgrounds/blue_blur.jpg	TRUE	
background_color	array	#6c89b5	TRUE	Set a background color.
background_image_enabled	boolean	TRUE	TRUE	Enable use of background images.
logout_icon_visible	text	FALSE	TRUE	Set the visibility of the logout icon.
domain_color	text	#ffffff	FALSE	Set the text color (and opacity) for domain name.
domain_color_hover	text	#69e5ff	FALSE	Set the text hover color (and opacity) for domain name.
logout_icon_color	text	#ffffff	FALSE	Set the color (and opacity) for the logout icon (if visible).
logout_icon_color_hover	text	#69e5ff	FALSE	Set the hover color (and opacity) for the logout icon (if visible).
menu_main_toggle_color	text	#ffffff	FALSE	Set the color (and opacity) for the menu toggle icon (in mobile view).
footer_background_color	text	rgba(0,0,0,0.1)	TRUE	Set the background color (and opacity) for the footer bar.
footer_color	text	rgba(255,255,255,0.1)	FALSE	Set the text color (and opacity) for the footer bar.

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
footer_border_radius	text	0 0 4px 4px	FALSE	Set the border radius of the footer bar.
message_default_background_color	text	#fafafa	TRUE	Set the background color for the positive (default) message bar.
message_default_color	text	#666	TRUE	Set the text color for the positive (default) message bar text.
message_positive_background_color	text	#ccffcc	TRUE	Set the background color for the positive (positive) message bar.
message_positive_color	text	#004200	TRUE	Set the text color for the positive (positive) message bar text.
message_negative_background_color	text	#ffcdcd	TRUE	Set the background color for the negative message bar.
message_negative_color	text	#670000	TRUE	Set the text color for the negative message bar text.
message_alert_background_color	text	#ffe585	TRUE	Set the background color for the alert message bar.
message_alert_color	text	#d66721	TRUE	Set the text color for the alert message bar text.
message_opacity	text	0.9	TRUE	Set the opacity of the message bar (decimal).
body_shadow_color	text	#000000	TRUE	Set the color (and opacity) of the body.
body_border_radius	text	4px	FALSE	Set the border radius of the body.
cache	boolean	FALSE	FALSE	Set whether to cache the theme in the session.
logo_align	text	center	FALSE	Set the alignment of the header logo (Inline menu only)
menu_main_background_color	text	#ff0000	FALSE	Set a background color (and opacity) of the main menu bar.
menu_main_background_color_hover	text	#ff0000	FALSE	Set a background hover color (and opacity) of the main menu items.
menu_main_icons	boolean	FALSE	FALSE	Show icons next to main menu items.
menu_main_background	text	/themes/default/ima	FALSE	Set a background

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
ound_image		ges/background_black.png		image for the main menu bar.
menu_main_shadow_color	text	#000000	TRUE	Set the shadow color (and opacity) of the main menu bar.
menu_main_text_color	text	#ffffff	FALSE	Set the text color of the main menu items.
menu_main_text_color_hover	text	#69e5ff	FALSE	Set the text hover color of the main menu items.
menu_main_text_font	text	Arial	FALSE	Set the font of the main menu items.
menu_main_text_size	text	10.25pt	FALSE	Set the text size of the main menu items.
menu_main_border_size	text	1px	FALSE	Set the border size of the main menu.
menu_main_border_color	text	#ffffff	FALSE	Set the border color (and opacity) of the main menu.
menu_position	text	top	TRUE	Set the position of the main menu (Fixed menu only).
menu_style	text	fixed	TRUE	Set the style of the main menu.
menu_sub_background_color	text	#000000	FALSE	Set the background color (and opacity) of the sub menus.
menu_sub_icons	boolean	FALSE	TRUE	Show indicator icons next to selected sub menu items.
menu_sub_shadow_color	text	#000000	TRUE	Set the shadow color (and opacity) of sub menus.
menu_sub_text_color	text	#ffffff	FALSE	Set the text color (and opacity) of sub menu items.
menu_sub_text_color_hover	text	#69e5ff	FALSE	Set the hover text color (and opacity) of sub menu items.
menu_sub_text_font	text	Arial	FALSE	Set the font of the sub menu items.
menu_sub_text_size	text	10pt	FALSE	Set the text size of the sub menu items.
menu_sub_border_radius	text	0 0 4px 4px	FALSE	Set the border radius of the sub menu.
menu_sub_border_size	text	1px	FALSE	Set the border size of the sub menu.
heading_text_font	text	arial	FALSE	Set the font of the page heading text.
heading_text_size	text	15px	FALSE	Set the size of the page heading text.

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
heading_text_color	text	#952424	FALSE	Set the color (and opacity) of the page heading text.
body_text_font	text	arial	FALSE	Set the font of body text.
body_text_color	text	#5f5f5f	FALSE	Set the color (and opacity) of the body text.
text_link_color	text	#004083	FALSE	Set the link color (and opacity) of text links outside tables.
text_link_color_hover	text	#5082ca	FALSE	Set the hover color (and opacity) of text links outside tables.
table_heading_text_font	text	arial	FALSE	Set the text font of table header rows.
table_heading_text_size	text	12px	FALSE	Set the text size of table header rows.
table_heading_background_color	text	#ffffff	FALSE	Set the background color (and opacity) of table header rows.
table_heading_border_color	text	#a4aebf	FALSE	Set the bottom border color (and opacity) of table header rows.
table_row_text_font	text	arial	FALSE	Set the text font of table data rows.
table_row_text_size	text	12px	FALSE	Set the text size of table data rows.
table_row_text_color	text	#000	FALSE	Set the text color (and opacity) of table data rows.
table_row_background_color_dark	text	#e5e9f0	FALSE	Set the darker background color (and opacity) of table data rows.
table_row_background_color_medium	text	#f0f2f6	FALSE	Set the medium background color (and opacity) of table data rows.
table_row_border_color	text	#c5d1e5	FALSE	Set the bottom border (dividing line) color (and opacity) of table data rows.
dashboard_border_color	text	#dbe0ea	FALSE	Set the border color (and opacity) of the Dashboard blocks.
dashboard_border_color_hover	text	#cbd3e1	FALSE	Set the border hover color (and opacity) of the Dashboard block.
dashboard_border_radius	text	5px	FALSE	Set the border radius of the

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
				Dashboard block.
dashboard_heading_background_color	text	#8e96a5	FALSE	Set the background color (and opacity) of the Dashboard block heading.
dashboard_heading_background_color_hover	text	#969dab	FALSE	Set the background hover color (and opacity) of the Dashboard block heading.
dashboard_heading_text_color	text	#ffffff	FALSE	Set the color (and opacity) of the Dashboard block heading text.
dashboard_heading_text_color_hover	text	#ffffff	FALSE	Set the hover color (and opacity) of the Dashboard block heading text.
dashboard_heading_text_size	text	10.5pt	FALSE	Set the size of the Dashboard block heading text.
dashboard_heading_text_shadow_color	text	#000000	FALSE	Set the shadow color (and opacity) of the Dashboard block heading text.
dashboard_heading_text_shadow_color_hover	text	#000000	FALSE	Set the shadow hover color (and opacity) of the Dashboard block heading text.
dashboard_number_background_color	text	#a4aebf	FALSE	Set the background color (and opacity) of the Dashboard block number.
dashboard_number_background_color_hover	text	#aeb7c5	FALSE	Set the background hover color (and opacity) of the Dashboard block number.
dashboard_number_text_color	text	#ffffff	FALSE	Set the color (and opacity) of the Dashboard block number.
dashboard_number_text_color_hover	text	#ffffff	FALSE	Set the hover color (and opacity) of the Dashboard block number.
dashboard_number_text_font	text	Calibri, Candara, Segoe, Segoe UI, Optima, Arial, sans-serif	FALSE	Set the font of the Dashboard block number.
dashboard_number_text_size	text	60pt	FALSE	Set the size of the Dashboard block number.
dashboard_number_text_shadow_color	text	#737983	FALSE	Set the shadow color (and opacity) of the Dashboard

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
				block number.
dashboard_number_title_text_color	text	#ffffff	FALSE	Set the color (and opacity) of the Dashboard block number title.
dashboard_number_title_text_font	text	Calibri, Candara, Segoe, Segoe UI, Optima, Arial, sans-serif	FALSE	Set the font of the Dashboard block number title.
dashboard_number_title_text_size	text	14px	FALSE	Set the size of the Dashboard block number title.
dashboard_number_title_text_shadow_color	text	#737983	FALSE	Set the shadow color (and opacity) of the Dashboard block number title.
dashboard_detail_header_text_size	text	11px	FALSE	Set the size of the Dashboard block detail header text.
dashboard_detail_row_text_size	text	11px	FALSE	Set the size of the Dashboard block detail row text.
dashboard_detail_shadow_color	text	#737983	FALSE	Set the shadow color of the Dashboard block detail box.
dashboard_detail_background_color_center	text	#f9fbfe	FALSE	Set the center gradient color of the Dashboard block detail area.
dashboard_footer_block_background_color_hover	text	#ebee3	FALSE	Set the background hover color (and opacity) of the Dashboard block footer bar.
dashboard_footer_block_dots_color	text	#a4aebf	FALSE	Set the color (and opacity) of the Dashboard block footer bar dots.
dashboard_footer_block_dots_color_hover	text	#a4aebf	FALSE	Set the hover color (and opacity) of the Dashboard block footer bar dots.
form_table_label_padding	text	7px 8px	FALSE	Set the padding of the form label cell.
form_table_label_background_color	text	#e5e9f0	FALSE	Set the background color (and opacity) of the form label cell.
form_table_label_border_color	text	#ffffff	FALSE	Set the bottom-border color (and opacity) of the form label cell.
form_table_label_border_radius	text	4px	FALSE	Set the border radius of the form label cell.
form_table_label_text_size	text	9pt	FALSE	Set the text size of

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
xt_size				the form label.
form_table_label_text_font	text	Arial	FALSE	Set the text font of the form label.
form_table_label_text_color	text	#000000	FALSE	Set the text color (and opacity) of the form label.
form_table_label_required_border_color	text	#cbcf5	FALSE	Set the right-border color (and opacity) of the required form label cell.
form_table_label_required_text_color	text	#000000	FALSE	Set the text color (and opacity) of the required form label.
form_table_label_required_text_weight	text	bold	FALSE	Set the text weight of the required form label.
form_table_field_padding	text	6px	FALSE	Set the padding of the form field cell.
form_table_field_background_color	text	#ffffff	FALSE	Set the background color (and opacity) of the form field cell.
form_table_field_bottom_border_color	text	#e5e9f0	FALSE	Set the bottom-border color (and opacity) of the form field cell.
form_table_field_bottom_border_radius	text	0	FALSE	Set the border radius of the form label cell.
form_table_field_text_size	text	8pt	FALSE	Set the size of text in the form field cell.
form_table_field_text_font	text	Arial	FALSE	Set the font of text in the form field cell.
form_table_heading_padding	text	8px 8px 4px 8px	FALSE	Set the padding of form column headings.
form_table_row_padding	text	3px 0	FALSE	Set the padding of form row cells.
form_table_row_text_size	text	9pt	FALSE	Set the size of text in the form rows.
login_background_color	array	#6c89b5	FALSE	Set the background color of the login page.
login_background_color	array	#144794	FALSE	Set a secondary background color of the login page, for a gradient effect.
login_background_image_enabled	boolean	TRUE	FALSE	Enable use of background images on the login page.
login_body_background_color	text	rgba(255,255,255,0.3)	TRUE	Set the background color for the login box.
login_body_shadow_color	text	rgba(140,140,140,0.3)	TRUE	Set the shadow color of the login

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
				box.
login_body_padding	text	30px	FALSE	Set the padding of the login box.
login_body_width	text	100%	FALSE	Set the width of the login box.
login_body_border_size	text	1px	FALSE	Set the border size of the login box.
login_body_border_color	text	#ffffff	FALSE	Set the border color (and opacity) of the login box.
login_link_text_color	text	#004083	FALSE	Set the color (and opacity) of text links on the login box.
login_link_text_color_hover	text	#5082ca	FALSE	Set the hover color (and opacity) of text links on the login box.
login_link_text_size	text	11px	FALSE	Set the size of text links on the login box.
login_link_text_font	text	Arial	FALSE	Set the font of text links on the login box.
button_background_color_bottom	text	#000000	FALSE	Set the background bottom color (and opacity) of buttons.
button_background_color_hover	text	#000000	FALSE	Set the background main/top hover color (and opacity) of buttons.
button_background_color_bottom_hover	text	#000000	FALSE	Set the background bottom hover color (and opacity) of buttons.
button_border_size	text	1px	FALSE	Set the border size of buttons.
button_border_color	text	#242424	FALSE	Set the border color (and opacity) of buttons.
button_border_color_hover	text	#000000	FALSE	Set the border hover color (and opacity) of buttons.
button_border_radius	text	3px	FALSE	Set the border radius of buttons.
button_text_size	text	11px	FALSE	Set the size of button text.
button_text_color	text	#ffffff	FALSE	Set the color (and opacity) of button text.
button_text_weight	text	bold	FALSE	Set the weight of button text.
button_padding	text	5px 8px	FALSE	Set the padding of buttons.
button_height	text	28px	FALSE	Set the height of buttons.
input_border_color	text	#c0c0c0	FALSE	Set the border color

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
				(and opacity) of text inputs.
input_border_color_hover	text	#c0c0c0	FALSE	Set the border hover color (and opacity) of text inputs.
input_border_color_focus	text	#c0c0c0	FALSE	Set the border focus color (and opacity) of text inputs.
input_border_size	text	1px	FALSE	Set the border size of text inputs.
input_border_radius	text	3px	FALSE	Set the border radius of text inputs.
input_shadow_inner_color	text	#cddaf0	TRUE	Set the inner shadow color (and opacity) of text inputs.
input_shadow_outer_color	text	#ffffff	FALSE	Set the outer shadow color (and opacity) of text inputs.
input_shadow_outer_color_focus	text	#cddaf0	TRUE	Set the outer focus shadow color (and opacity) of text inputs.
input_text_size	text	12px	FALSE	Set the size of text input content.
input_text_font	text	Arial	FALSE	Set the font of text input content.
input_text_color	text	#000000	FALSE	Set the color (and opacity) of text input content.
input_text_placeholder_color	text	#999999	FALSE	Set the color (and opacity) of input placeholder text.
login_input_background_color	text	#ffffff	FALSE	Set the background color (and opacity) of text inputs on the login box.
login_input_border_color	text	#c0c0c0	FALSE	Set the border color (and opacity) of text inputs on the login box.
login_input_border_color_focus	text	#c0c0c0	FALSE	Set the border focus color (and opacity) of text inputs on the login box.
login_input_border_size	text	1px	FALSE	Set the border size of text inputs on the login box.
login_input_border_radius	text	3px	FALSE	Set the border radius of text inputs on the login box.
login_input_shadow	text	#cddaf0	FALSE	Set the inner

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
_inner_color				shadow color (and opacity) of text inputs on the login box.
login_input_shadow_inner_color_focus	text	#ffffff	FALSE	Set the inner focus shadow color (and opacity) of text inputs on the login box.
login_input_shadow_outer_color	text	#ffffff	FALSE	Set the outer shadow color (and opacity) of text inputs on the login box.
login_input_shadow_outer_color_focus	text	#cddaf0	FALSE	Set the outer focus shadow color (and opacity) of text inputs on the login box.
login_input_text_size	text	12px	FALSE	Set the size of text input content on the login box.
login_input_text_font	text	Arial	FALSE	Set the font of text input content on the login box.
login_input_text_placeholder_color	text	#999999	FALSE	Set the color (and opacity) of input placeholder text on the login box.
font_loader	text	TRUE	FALSE	Enables the dynamic loading of web fonts (requires an Internet connection).
font_loader_version	text	1.6.16	FALSE	Set the web font loader version to use - specific (e.g. 1.6.16) or latest in branch (e.g. 1).
font_retrieval	text	asynchronous	FALSE	Set the retrieval method for the web font loader (default: synchronous).
font_source_key	text		FALSE	API key that allows access to the available fonts list.
body_icon_color	text	rgba(255,255,255,0.25)	FALSE	Set the color (and opacity) for the icons in the body.
body_icon_color_hover	text	rgba(255,255,255,0.50)	FALSE	Set the hover color (and opacity) for the icons in the body.
menu_brand_type	text	image	FALSE	
background_color	array	#144794	TRUE	Set a secondary background color, for a gradient

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
				effect.
domain_visible	text	TRUE	TRUE	Set the visibility of the name of the domain currently being managed.
menu_main_toggle_color_hover	text	#69e5ff	FALSE	Set the hover color (and opacity) for the menu toggle icon (in mobile view).
message_delay	text	1.75	TRUE	Set the hide delay of the message bar (seconds).
domain_selector_shadow_color	text	#888888	TRUE	Set the shadow color (and opacity) of the domain selector pane.
menu_main_border_radius	text	0 0 4px 4px	FALSE	Set the border radius of the main menu.
menu_sub_background_color_hover	text		FALSE	Set the hover background color (and opacity) of the sub menu items.
menu_sub_border_color	text	#ffffff	FALSE	Set the border color (and opacity) of the sub menu.
body_text_size	text	12px	FALSE	Set the size of the body text.
table_heading_text_color	text	#3164ad	FALSE	Set the text color (and opacity) of table header rows.
table_row_background_color_light	text	#fff	FALSE	Set the lighter background color (and opacity) of table data rows.
dashboard_heading_text_font	text	Calibri, Candara, Segoe, Segoe UI, Optima, Arial, sans-serif	FALSE	Set the font of the Dashboard block heading text.
dashboard_number_text_shadow_color_hover	text	#737983	FALSE	Set the shadow hover color (and opacity) of the Dashboard block number.
dashboard_detail_background_color_edge	text	#edf1f7	FALSE	Set the edge gradient color of the Dashboard block detail area.
dashboard_footer_background_color	text	#e5e9f0	FALSE	Set the background color (and opacity) of the Dashboard block footer bar.
form_table_label_required_background_color	text	#e5e9f0	FALSE	Set the background color of the required form label cell.

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
form_table_field_text_color	text	#666666	FALSE	Set the color (and opacity) of text in the form field cell.
login_body_border_radius	text	4px	FALSE	Set the border radius of the login box.
button_background_color	text	#4f4f4f	FALSE	Set the background main/top color (and opacity) of buttons.
button_text_font	text	Candara, Calibri, Segoe, Segoe UI, Optima, Arial, sans-serif	FALSE	Set the font of button text.
button_text_color_hover	text	#ffffff	FALSE	Set the hover color (and opacity) of button text.
input_background_color	text	#ffffff	FALSE	Set the background color (and opacity) of text inputs.
input_shadow_inner_color_focus	text	#ffffff	FALSE	Set the inner focus shadow color (and opacity) of text inputs.
login_input_border_color_hover	text	#c0c0c0	FALSE	Set the border hover color (and opacity) of text inputs on the login box.
login_input_text_color	text	#000000	FALSE	Set the color (and opacity) of text input content on the login box.
body_color	text	rgba(255,255,255,0.77)	TRUE	Set then body background color (and opacity) of the content.
background_image	array	/themes/default/images/backgrounds/yellowstone_3.jpg	FALSE	

Time Conditions

FusionPBX menu [Apps > Time Conditions](#)

Time Conditions specific default settings.

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
region	text	usa	TRUE	What region to use by default when choosing Time Conditions
preset_england	array	{ "new_years_day":	TRUE	England Holiday

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
		{"mday": "1", "mon": "1"}}		
preset_england	array	{"may_day": {"mon": "5", "mday": "1-7", "wday": "2"}}	TRUE	England Holiday
preset_england	array	{"august_bank_holiday": {"mon": "8", "mday": "25-31", "wday": "2"}}	TRUE	England Holiday
preset_england	array	{"christmas_day": {"mday": "25", "mon": "12"}}	TRUE	England Holiday
preset_england	array	{"boxing_day": {"mday": "26", "mon": "12"}}	TRUE	England Holiday
preset_usa	array	{"new_years_day": {"mday": "1", "mon": "1"}}	TRUE	USA Holiday
preset_usa	array	{"presidents_day": {"wday": "2", "mon": "2", "mday": "15-21"}}	TRUE	USA Holiday
preset_usa	array	{"memorial_day": {"mday": "25-31", "wday": "2", "mon": "5"}}	TRUE	USA Holiday
preset_usa	array	{"independence_day": {"mday": "4", "mon": "7"}}	TRUE	USA Holiday
preset_usa	array	{"labor_day": {"wday": "2", "mon": "9", "mday": "1-7"}}	TRUE	USA Holiday
preset_usa	array	{"columbus_day": {"wday": "2", "mon": "10", "mday": "8-14"}}	TRUE	USA Holiday
preset_usa	array	{"veterans_day": {"mday": "11", "mon": "11"}}	TRUE	USA Holiday
preset_usa	array	{"black_friday": {"wday": "6", "mon": "11", "mday": "23-29"}}	TRUE	USA Holiday
preset_usa	array	{"christmas_day": {"mday": "25", "mon": "12"}}	TRUE	USA Holiday
preset_canada	array	{"new_years_day": {"mday": "1", "mon": "1"}}	TRUE	Canada Holiday
preset_canada	array	{"family_day": {"wday": "2", "mon": "2", "mday": "8-14"}}	TRUE	Canada Holiday
preset_canada	array	{"victoria_day": {"wday": "2", "mon": "5", "mday": "18-24"}}	TRUE	Canada Holiday
preset_canada	array	{"canada_day": {"mday": "1", "mon": "7"}}	TRUE	Canada Holiday

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
		}}		
preset_canada	array	{"bc_day":{"wday":"2","mon":"8","mday":"1-7"}}	TRUE	Canada Holiday
preset_canada	array	{"remembrance_day":{"mday":"11","mon":"11"}}	TRUE	Canada Holiday
preset_canada	array	{"christmas_day":{"mday":"25","mon":"12"}}	TRUE	Canada Holiday
preset_canada	array	{"boxing_day":{"mday":"26","mon":"12"}}	TRUE	Canada Holiday
preset_canada	array	{"labour_day":{"wday":"2","mon":"9","mday":"1-7"}}	TRUE	Canada Holiday
preset_england	array	{"spring_bank_holiday":{"mon":"5","mday":"25-31","wday":"2"}}	TRUE	England Holiday
preset_usa	array	{"martin_luther_king_jr_day":{"wday":"2","mon":"1","mday":"15-21"}}	TRUE	USA Holiday
preset_usa	array	{"thanksgiving_day":{"wday":"5","mon":"11","mday":"22-28"}}	TRUE	USA Holiday
preset_canada	array	{"thanksgiving_day":{"wday":"2","mon":"10","mday":"8-14"}}	TRUE	Canada Holiday

User

FusionPBX menu [Accounts > Users](#)

User specific default settings.

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
password_special	boolean	FALSE	TRUE	Set whether to require at least one special character in user passwords.
unique	text	global	FALSE	Make all user names unique on all domains.
password_length	numeric	10	TRUE	The default length of characters in a user password.
password_number	boolean	TRUE	TRUE	Set whether to require at least one

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
				number in user passwords.
password_lowercase	boolean	TRUE	TRUE	Set whether to require at least one lowercase letter in user passwords.
password_uppercase	boolean	TRUE	TRUE	Set whether to require at least one uppercase letter in user passwords.

[Voicemail](#)

FusionPBX menu [Apps > Voicemail](#)

Voicemail specific default settings.

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
voicemail_file	text	attach	TRUE	Define whether to attach voicemail files to email notifications, or only include a link.
keep_local	boolean	TRUE	TRUE	Define whether to keep voicemail files on the local system after sending attached via email.
storage_type	text	base64	FALSE	Define which storage type (base_64 stores in the database).
message_max_length	numeric	300	TRUE	Maximum length of a voicemail (in seconds).
password_length	numeric	8	TRUE	The default length of characters in a voicemail password.
display_domain_name	boolean	TRUE	FALSE	Enable display of @domain_name after voicemail_id when rendering emails.
remote_access	boolean	FALSE	TRUE	Allow access to the voicemail menu with the correct voicemail password.
message_order	text	asc	TRUE	Set message order to asc to play oldest message first or desc to play newest message first.

Advanced

Default Setting Subcategory	Default Setting Name	Default Setting Value	Default Setting Enabled	Default Setting Description
password_complexity	boolean	TRUE	FALSE	Enforce voicemail password complexity.
password_min_length	numeric	4	FALSE	Minimum voicemail password length.
smtp_from	text		TRUE	SMTP From: specific to Voicemail.
smtp_from_name	text		TRUE	SMTP From: Name specific to Voicemail.
not_found_message	boolean	FALSE	TRUE	Default for not found message.
greeting_max_length	numeric	90	TRUE	Maximum length of a voicemail greeting (in seconds).

[Next](#) [Previous](#)

Unieke FAQ ID: #4051

Auteur: Helpdesk

Laatst bijgewerkt: 2022-11-28 10:24